

## FEATURES

- 1/3"Sony Double Scan CCD
- Wide Dynamic Range
- Super High Resolution 600 TV Lines
- Minimum Illumination:0.001 Lux/F1.2
- Day & Night With ICR (Infrared Cut Filter Removal)
- Built in Samsung DSP
- RS-485 Remote Setup Control
- Video Intelligent
- Digital Image Stabilization
- Privacy zone/Motion Detection/Mirror/OSD



1/3 INCH SONY CCD



WIDE DYNAMIC RANGE



SUPER HIGH RESOLUTION 600 TVL



MINIMUM ILLUMINATION:0.001 Lux



VIDEO INTELLIGENT



EXTENDED DYNAMIC RANGE



DIGITAL IMAGE STABILIZATION



DIGITAL NOISE REDUCTION



X 256 TIMES SENS-UP



MULTI PRIVACY ZONE



Samsung Technology NEW DSP

## INTELLIGENT BOX CAMERA SBC-1435

### TECHNICAL INFORMATION

|                             |                                 |
|-----------------------------|---------------------------------|
| Model                       | SBC-1435                        |
| Signal System               | PAL                             |
| Image Sensor                | 1/3"Sony Double Scan CCD        |
| No Of Effective Pixels      | 752 (H) X 582(V)                |
| WDR                         | YES                             |
| Day / Night                 | ICR / SENSUP                    |
| Horizontal Resolution       | 600 TVL                         |
| Minimum Illumination        | 0.001 Lux/F1.2                  |
| Video Intelligent           | Fixed / Move                    |
| Digital Image Stabilization | Yes                             |
| Extended Dynamic Range      | Yes                             |
| Digital Noise Reduction     | Yes                             |
| Sens-up                     | X 256                           |
| Advance Motion Detection    | Yes                             |
| Privacy zone Masking        | 8 Zone                          |
| Camera Control via Coaxial  | CCVC Technology                 |
| Digital Zoom                | On / Off (2X - 10X)             |
| Communication               | RS-485                          |
| AWB                         | Automatic /manual level control |
| Iris Control                | DC/ Video                       |
| Video output BNC            | BNC 1.0Vp-p 75ΩTerminated       |
| Operation Temperature       | -10°C to +50°C RH95%MAX         |
| Power Consumption           | DC 12V +/-10%                   |
| Dimension                   | 108(L)x65(W)x50(H)mm            |